## **Accessories**

Audible/visual hi-low temperature alarm, standard

- ~ With battery back-up
- ~ With relay for connection to a dialer

Audible/Visual hi-low temperature/RH alarm (for chambers with microprocessor-controlled RH only)

Access port, covered, 2" diameter

Access for wiring (Swagelok®)

Clock, digital, to control lights or microprocessor

Coated coil, to resist corrosive vapors

Control panel cover, lockable Plexiglas©

Data pack, mountable stainless steel instrument panel with temperature recorder and standard A/V temperature alarm (optional alarm relay)

Door, opaque (no light penetration)

Door lock, per hinged door or set of gliding doors

Drawers, stainless steel

~ Pull-out in one direction

Exterior light switch

Extra deep cabinet (31" interior/36" exterior), not available in single door sizes

Floor drain, 1.25" diameter

Hot gas bypass (HGBP), single or dual valves

Horizontal air flow ducts

Humidistat-controlled tap water humidity generator, ultrasonic RH

**Humidity** meter

Lamp set with two or three lights pigtailed together, one plug, fluorescent or LED

Microprocessor options (not available on standard refrigerators or freezer)

- Retransmit output (0-5, 1-5, 0-10 vDC, or 0-20, 4-20 mAmp)
- ~ RS232 port

Outlet, vapor-proof duplex

Pass-thru options, not available on single-door models

Power switch, key on/off

Remote compressor package

Seismic bolting kit

Shelf, epoxy-coated steel wire, size depends on model: 21" x 17", 24" x 24", 24" x 28", or 24"x 32"

Stainless steel interior or exterior

Temperature control, multipoint ramp and soak processor

Thermoelectric (Peltier) cooling for some applications

Thermometer, temperature recording, 6" seven day

Thermometer, temperature/RH recording, 10" seven day (for chambers with microprocessor-controlled RH only)

Ventilation system, fresh air for plants/animals

Vibration reduction package

Voltage conversions, to 230V/50h, 220V/50h, 220V/60h

Wooden crate, for export



654 Petrolia Road, Toronto, ON M3J 2W3 Tel: (416) 736-6166

Toll-Free: (800) 387 3570 Fax: (416) 736-9346